

HD 60-800F High Density Polyethylene

SureSpec HD 60-800F is a certified prime grade resin designed for production of extrusion coating used in general food packaging. **HD 60-800F** features a combination of excellent MVTR, good processability, grease resistance, low gel levels and improved stiffness and scuff resistance. **HD 60-800F** complies with FDA regulation 21CFR 177.1520 and with most international regulations concerning the use of Polyethylene in contact with food articles.

PROPERTIES	ASTM	UNIT	NOMINAL VALUES
RESIN			
Melt Flow Rate (190 °C, 2.16kg)	D1238	g/10 min	8.0
Density	D1505	g/cm ³	0.962

Typical Value of Properties not to be construed as specifications

* Test Made on injection molded Type 1 tension test specimen according to ASTM D2146

1 - 1% secant @ 0.051 in/min. speed.

2 - @ 2 in/min.



The technical information, suggested uses and applications presented are made without charge and are believed to be reliable; however, the Ravago Group* disclaims responsibility for reliance and results of use of this information. THE RAVAGO GROUP DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT(S) DESCRIBED HEREINABOVE, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Ravago Group expressly disclaims any statements or suggestions as being inducement. All users should rely upon their own knowledge and testing in determining product suitability.